



PBZ LLC
295 Wood Corner Rd.
Lititz, PA 17543
717-738-7365
KickoutFlashing.com

This suggested specification has been prepared by PBZ LLC, manufacturers of Kickout Flashing. Kickout Flashing is a pre-cut and welded aluminum piece that is inserted as a rain diverter where a sloped roof line meets a vertical wall.

Please contact us directly for an editable version of this document.

SECTION 07 71 40

ALUMINUM KICKOUT FLASHING

PART 1 GENERAL

1.1 SUMMARY

- A. Provide kickout flashing (rain water diverter) at any connection of sloped roofing and vertical wall. Rain water to be diverted to gutter utilizing kickout flashing.

1.2 SUBMITTALS

- A. Product Data: Manufacturer's product data to be used, including:
 1. Preparation instructions and recommendations.
 2. Storage and handling requirements and recommendations.
 3. Installation methods.

1.3 QUALITY ASSURANCE

- A. Comply with governing codes and regulations. Material preference for product is aluminum (either uncoated or powder coated.)

1.4 DELIVERY, STORAGE AND HANDLING

- A. Deliver, store and handle materials and products in strict compliance with manufacturer's instructions and recommendations and industry standards. Protect from damage.
- B. Store products in manufacturer's labeled packaging until ready for installation.

PART 2 PRODUCTS

2.1 MATERIALS

- A. Manufacturer: Kickout Flashing by PBZ LLC, 295 Wood Corner Rd., Lititz, PA 17543, 717-738-7365, KickoutFlashing.com
- B. Substitutions: As equal. Requests for substitutions will be considered in accordance with provisions of Section 01 60 00 - Product Requirements.
- C. Material shall be 3003-H14 aluminum, with a thickness of 0.040," pre-formed and

welded to size 6" x 6" x 10." Material shall not be field-formed.

- D. Material shall be uncoated or powder coated aluminum.
- E. Powder coated colors: black, dark brown, gray, sand, tan, white. Powder coating to meet AAMA 2604 specifications.
- F. Material to meet or exceed ENERGY STAR Version 3 National Program Requirements for Water Management.

PART 3 EXECUTION

3.1 PREPARATION

- A. Prepare substrates for attachment of kickout flashing.

3.2 INSTALLATION

- A. Install in accordance with manufacturer's installation instructions and in proper relationship with adjacent construction.

3.3 CLEANING AND PROTECTION

- A. Protect installed products until completion of project.
- B. Clean product before Substantial Completion.

END OF SECTION